

10 & 15 MM MINIATURE VALVES

All of the benefits of Clippard quality and reliability are available in these 10 mm and 15 mm miniature valves. Offered in both Normally-Open or Normally-Closed models, these 2-Way and 3-Way valves are perfect for small areas where compact electronically-controlled pneumatics are needed.

A high strength, engineered lightweight glass-filled nylon body—along with stainless steel, FKM and nitrile—makes this series suitable for a broad range of applications. With exceptional life and reliability, this versatile miniature valve is a smart choice for many types of systems across many different industries.



10 MM STANDARD

Direct operating valves well-suited for single- or multiple-valve mounting in small spaces.
(90° connector shown)



15 MM STANDARD

Direct operating valves well-suited for single- or multiple-valve mounting in small spaces.
(DIN connector shown)



10 MM LATCHING

A short pulse of current shifts this valve which “latches” indefinitely; another pulse returns the valve.
(Wire leads shown)



15 MM LATCHING

A short pulse of current shifts this valve which “latches” indefinitely; another pulse returns the valve.
(Wire lead shown)



10 MM HIGH FLOW 2-WAY

Specialty series for high flow applications.
(In-line connector shown)



15 MM HIGH FLOW 2-WAY

Specialty series for high flow applications.
(In-line connector shown)



10 MM ISO 15218 SERIES

Conforms to ISO standard for mounting and port locations.
(90° connector shown)

Medium	Air, gas, or other compatible fluids
Material	Stainless steel core and springs, Nylon body, FKM dynamic seals, nitrile gasket and static seals
Electrical	The coil is constructed of copper wire and insulated according to the class "F" standard. All circuitry and connections are protected from corrosion
CE, RoHS Compliant	
More Details	clippard.com/link/10-15mm

