

## 50 Electronic Valves – 10 mm + 15 mm Miniature Valves



This numbering schematic is shown for illustration purposes only. All possible configurations are not available. For standard models, see the products illustrated in this catalog.



Another feature of the Clippard 10 mm valve is the ability to detach the coil and connector from the valve body. This can be useful for the purpose of orientating the coil by 180°, or exchanging connector types or voltages.

All of the benefits of Clippard quality and reliability are now available in these 10 mm and 15 mm valves. Offered in both Normally-Open or Normally-Closed models, these 2/2 and 3/2 valves are perfect for small areas where compact electronically-controlled pneumatics are needed.

This series has a high strength, engineered lightweight glass filled nylon body, along with stainless steel, copper and Buna-N, making it suitable for a broad range of applications. With exceptional life and reliability this is the perfect sub-miniature valve for tomorrow's needs in a wide variety of industries.

**All 10 mm and 15 mm valves are RoHS compliant.**

Numbering System				
Valve Type	Orifice Code	Power	Electrical Connection	Voltage
E210 - 2/2 N.C.	A - 0.5 mm	1 - 0.6 Watts	F - In-Line	012 - 12 VDC
E310 - 3/2 N.C.	C - 0.75 mm	2 - 1.3 Watts	C - In-Line with LED	024 - 24 VDC
E3010 - 3/2 N.O.			E - 90° L - 90° with LED W - Wire Leads, 300 mm	
<b>E210</b>	<b>A</b>	<b>-</b>	<b>1</b>	<b>C</b>
				<b>012</b>