

Order Information

Order Information									
G1/8 Ported or Mount	Manifold Mount (only)	Connector	12 VDC	24 VDC	24 VAC	110 VAC	220 VAC	Watt	Working Pressure
2-Way Valves									
M-EGV-2-E*	M-EGV-2M-E*	90° Connector	•	•					
M-EGV-2-L*	M-EGV-2M-L*	90° Connector with LED	•	•					
M-EGV-2-F*	M-EGV-2M-F*	In-Line Connector	•	•				0.6	1 to 7 bar
M-EGV-2-C*	M-EGV-2M-C*	In-Line Connector with LED	•	•					
M-EGV-2-W*	M-EGV-2M-W*	Wire Leads, 300 mm	•	•					
M-EGV-2-D*	M-EGV-2M-D*	DIN Connector	•	•	•	•	•	2.5	10 bar
3-Way Valves									
M-EGV-3-E*	M-EGV-3M-E*	90° Connector	•	•					
M-EGV-3-L*	M-EGV-3M-L*	90° Connector with LED	•	•					
M-EGV-3-F*	M-EGV-3M-F*	In-Line Connector	•	•				0.6	1 to 7 bar
M-EGV-3-C*	M-EGV-3M-C*	In-Line Connector with LED	•	•					
M-EGV-3-W*	M-EGV-3M-W*	Wire Leads, 300 mm	•	•					
M-EGV-3-D*	M-EGV-3M-D*	DIN Connector	•	•	•	•	•	2.5	10 bar

* Add Voltage Choice to the end of each Base Part Number. "012" (12 VDC), "024" (24 VDC) "24A" (24 VAC), "110" (110 VAC) or "220" (220 VAC). Example: M-EGV-2-E012

DIN Connectors

For Use with 15 mm Valves Only

DIN 43650 Form C Connectors with 8 mm spade center spacing mate with the 15 mm DIN connector coil. Available with or without surge suppression, and 150 or 380 mm PVC molded three-wire cord set.



Part No.	Volts	LED	Cord
CC-C CC-C-P6 CC-C-P15	6-240	no	150 mm 380 mm
CC-CLL CC-CLL-P6 CC-CLL-P15	6-24	yes	150 mm 380 mm
CC-CLM CC-CLM-P6 CC-CLM-P15	48-110	yes	150 mm 380 mm

