



## 52 Electronic Valves – 10 mm Miniature Valves

| Order Information   |                  |       |         |                    |             |
|---|------------------|-------|---------|--------------------|-------------|
| Type  | Working Pressure | Watts | Orifice | Connector          | Base No.    |
|  <p>2/2 Normally-Closed</p>  | 1 to 7 bar       | 0.6   | 0.5     | 90°                | E210A-1E *  |
|   | 0 to 7 bar       | 1.3   | 0.75    |                    | E210C-2E *  |
|   | 1 to 7 bar       | 0.6   | 0.5     | 90° with LED       | E210A-1L *  |
|   | 0 to 7 bar       | 1.3   | 0.75    |                    | E210C-2L *  |
|   | 1 to 7 bar       | 0.6   | 0.5     | In-Line            | E210A-1F *  |
|   | 0 to 7 bar       | 1.3   | 0.75    |                    | E210C-2F *  |
|   | 1 to 7 bar       | 0.6   | 0.5     | In-Line with LED   | E210A-1C *  |
|   | 0 to 7 bar       | 1.3   | 0.75    |                    | E210C-2C *  |
|   | 1 to 7 bar       | 0.6   | 0.5     | Wire Leads, 300 mm | E210A-1W *  |
|   | 0 to 7 bar       | 1.3   | 0.75    |                    | E210C-2W *  |
|  <p>3/2 Normally-Closed</p> | 1 to 7 bar       | 0.6   | 0.5     | 90°                | E310A-1E *  |
|   | 0 to 7 bar       | 1.3   | 0.75    |                    | E310C-2E *  |
|   | 1 to 7 bar       | 0.6   | 0.5     | 90° with LED       | E310A-1L *  |
|   | 0 to 7 bar       | 1.3   | 0.75    |                    | E310C-2L *  |
|   | 1 to 7 bar       | 0.6   | 0.5     | In-Line            | E310A-1F *  |
|   | 0 to 7 bar       | 1.3   | 0.75    |                    | E310C-2F *  |
|   | 1 to 7 bar       | 0.6   | 0.5     | In-Line with LED   | E310A-1C *  |
|   | 0 to 7 bar       | 1.3   | 0.75    |                    | E310C-2C *  |
|   | 1 to 7 bar       | 0.6   | 0.5     | Wire Leads, 300 mm | E310A-1W *  |
|   | 0 to 7 bar       | 1.3   | 0.75    |                    | E310C-2W    |
|  <p>3/2 Normally-Open</p>  | 1 to 5 bar       | 0.6   | 0.5     | 90°                | E3O10C-1E * |
|   | 0 to 7 bar       | 1.3   | 0.75    |                    | E3O10C-2E * |
|   | 1 to 5 bar       | 0.6   | 0.5     | 90° with LED       | E3O10A-1L * |
|   | 0 to 7 bar       | 1.3   | 0.75    |                    | E3O10C-2L * |
|   | 1 to 5 bar       | 0.6   | 0.5     | In-Line            | E3O10A-1F * |
|   | 0 to 7 bar       | 1.3   | 0.75    |                    | E3O10C-2F * |
|   | 1 to 5 bar       | 0.6   | 0.5     | In-Line with LED   | E3O10A-1C * |
|   | 0 to 7 bar       | 1.3   | 0.75    |                    | E3O10C-2C * |
|   | 1 to 5 bar       | 0.6   | 0.5     | Wire Leads, 300 mm | E3O10A-1W * |
|   | 0 to 7 bar       | 1.3   | 0.75    |                    | E3O10C-2W   |

\* Add Voltage Choice to the end of each Base Part Number. Example E210A-1E012