FSR-24-❑-❑

Single Acting

Mount: Front **Standard Stroke Lengths:** 1/2”, 1”, 1-1/2”, 2”, 3”, 4”
Type: Rotating Rod **Spring Compressed:** 10 lbs. **Spring At Rest:** 4 1/2 lbs.
Options: MB, B, H, V, S, N

For magnetic bumpers add .312
For S option add .187



SSN-24-❑-❑

Single Acting

Mount: Stud **Standard Stroke Lengths:** 1/2”, 1”, 1-1/2”, 2”, 3”, 4”
Type: Non-Rotating Rod **Spring Compressed:** 10 lbs. **Spring At Rest:** 4 1/2 lbs.
Options: MB, B, H, V, S, N

For magnetic bumpers add .312
For S option add .187



Nut included, but not shown on drawing

SSR-24-❑-❑

Single Acting

Mount: Stud **Standard Stroke Lengths:** 1/2”, 1”, 1-1/2”, 2”, 3”, 4”
Type: Rotating Rod **Spring Compressed:** 10 lbs. **Spring At Rest:** 4 1/2 lbs.
Options: MB, B, H, V, S, N

For magnetic bumpers add .312
For S option add .187



Nut included, but not shown on drawing

TSR-24-❑-❑

Single Acting

Mount: Trunnion **Standard Stroke Lengths:** 1/2”, 1”, 1-1/2”, 2”, 3”, 4”
Type: Rotating Rod **Spring Compressed:** 10 lbs. **Spring At Rest:** 4 1/2 lbs.
Options: MB, B, H, V, S, N

For magnetic bumpers add .312
For S option add .187