



MINIMATIC® SLIP-ON FITTINGS



Minimatic slip-on fittings provide a flexible, easy alternative to ferrule and push-to-connect design fittings.

Clippard Minimatic slip-on fittings are designed to be used with Clippard urethane hose. The flexibility and strength of urethane hose and the compact design of the fittings are ideal for pneumatic applications where convenience and size are considerations. The Minimatic slip-on fitting used with Clippard urethane hose will provide a leak free connection that will hold well beyond the working pressure of the hose without the need for additional clamps.

Minimatic slip-on fittings are available in a wide variety of configurations in a number of styles including tee, connectors, crosses, swivel, and universal. Barb sizes can be mixed on the same fitting for applications requiring multiple tubing sizes. The electroless nickel plating of Minimatic slip-on fittings provides corrosion resistance in applications involving high moisture, while enabling the fittings to retain their original, lustrous appearance.

Features







- Single barb design for quick and easy positive seal
- Miniature size provides low profile
- Multiple configurations for every need
- Electroless nickel plating
- Available with 1/16", 3/32" or 1/8" hose barb
- Available with #10-32 thread and 1/8" NPT
- Holds to the burst pressure of polyurethane hose

CONNECTOR FITTINGS







Material: Brass electroless nickel plated

Gasket: Buna-N gasket included with #10-32 threads except when ordered in bulk

Hose-to-Hose Connectors

C22  (2) 1/16" I.D. hose barb 0.656 1/4" sq.	C32 NEW!  3/32" I.D. hose barb 0.684 1/4" sq. 1/16" I.D. hose barb	C33 NEW!  (2) 3/32" I.D. hose barb 0.712 1/4" sq.
C42  1/16" I.D. hose barb 0.750 1/4" sq. 1/8" I.D. hose barb	C43 NEW!  3/32" I.D. hose barb 0.762 1/4" sq. 1/8" I.D. hose barb	C44  0.875 1/4" hex. (2) 1/8" I.D. hose barb

#10-32 to Hose Connectors

CT2 Gasket comes pre-installed  1/16" I.D. hose barb 0.468 1/4" hex. #10-32 thd.	CT3 NEW!  3/32" I.D. hose barb 0.523 1/4" hex. #10-32 thd.	CT4 Gasket comes pre-installed  1/8" I.D. hose barb 0.562 1/4" hex. #10-32 thd.
CT0-2 Gasket included. Not installed  1/4" sq. 0.468 1/16" I.D. hose barb #10-32 thd.	CT0-3 NEW!  1/4" sq. 0.468 3/32" I.D. hose barb #10-32 thd.	CT0-4 Gasket included. Not installed  1/4" sq. 0.468 1/8" I.D. hose barb #10-32 thd.