









MINIMATIC® SLIP-ON FITTINGS

SWIVEL FITTINGS

























Hose to Hose Swivel "T" Fittings

Material: Brass electroless nickel plated

Gasket: Buna-N gasket included with #10-32 threads except when ordered in bulk

<p>S42-2</p> 	 <p>0.531 1.062 2(2)1/16" I.D. hose barb 5/16" hex. 1/8" I.D. hose barb</p>	<p>S44-4</p> 	 <p>0.656 1.187 2(3)1/8" I.D. hose barb 5/16" hex.</p>	<p>S40-4004</p> 	 <p>0.937 0.875 5/16" hex. (3)1/8" I.D. hose barb</p>
---	--	---	--	--	--

#10-32 to Hose Swivel "T" Fittings

<p>ST0-2002</p> 	 <p>0.718 0.718 2(2)1/16" I.D. hose barb 5/16" hex. #10-32 thd.</p>	<p>ST0-3003</p> 	<p>NEW!</p>  <p>0.801 0.718 2(2) 3/32" ID hose barb 5/16" hex. #10-32 thd.</p>	<p>ST0-4004</p> 	 <p>0.937 0.718 2(2)1/8" I.D. hose barb 5/16" hex. #10-32 thd.</p>
<p>ST2-2</p> 	 <p>0.531 0.937 2(2)1/16" I.D. hose barb 5/16" hex. #10-32 thd.</p>	<p>ST3-3</p> 	<p>NEW!</p>  <p>0.580 0.961 2(2) 3/32" I.D. hose barb 5/16" hex. #10-32 thd.</p>	<p>ST4-4</p> 	 <p>0.656 1.187 2(2)1/8" I.D. hose barb 5/16" hex. #10-32 thd.</p>
<p>SP0-2002</p> 	 <p>0.718 0.843 2(2)1/16" I.D. hose barb 7/16" hex. 1/8-27 NPT</p>	<p>SP0-3003</p> 	<p>NEW!</p>  <p>0.812 0.843 2(2) 3/32" I.D. hose barb 7/16" hex. 1/8-27 NPT</p>	<p>SP0-4004</p> 	 <p>0.656 0.843 2(2)1/8" I.D. hose barb 7/16" hex. 1/8-27 NPT</p>
<p>SP2-2</p> 	 <p>0.625 1.031 2(2)1/16" I.D. hose barb 7/16" hex. 1/8-27 NPT</p>	<p>SP3-3</p> 	<p>NEW!</p>  <p>0.656 1.062 2(2) 3/32" I.D. hose barb 7/16" hex. 1/8-27 NPT</p>	<p>SP4-4</p> 	 <p>0.718 1.156 2(2)1/8" I.D. hose barb 7/16" hex. 1/8-27 NPT</p>

Tip Most Clippard #10-32 threaded fittings require no more than 9 inch pounds of torque to seal. We recommend that this force not be exceeded.