

# 1 1/16" BORE STAINLESS STEEL CYLINDER




## FSR-17-□-□

Single Acting

**Mount:** Front      **Standard Stroke Lengths:** 1/2", 1", 1-1/2", 2", 3", 4"  
**Type:** Rotating Rod      **Spring Compressed:** 7 lbs. **Spring At Rest:** 2 lbs.  
**Options:** MB, B, H, V, S, N      For magnetic bumpers add .312

For S option add .250




## SSN-17-□-□

Single Acting

**Mount:** Stud      **Standard Stroke Lengths:** 1/2", 1", 1-1/2", 2", 3", 4"  
**Type:** Non-Rotating Rod      **Spring Compressed:** 7 lbs. **Spring At Rest:** 2 lbs.  
**Options:** MB, B, H, V, S, N      For magnetic bumpers add .312

For S option add .250




Nut included, but not shown on drawing

## SSR-17-□-□

Single Acting

**Mount:** Stud      **Standard Stroke Lengths:** 1/2", 1", 1-1/2", 2", 3", 4"  
**Type:** Rotating Rod      **Spring Compressed:** 7 lbs. **Spring At Rest:** 2 lbs.  
**Options:** MB, B, H, V, S, N      For magnetic bumpers add .312

For S option add .250



Nut included, but not shown on drawing

## TSR-17-□-□

Single Acting

**Mount:** Trunnion      **Standard Stroke Lengths:** 1/2", 1", 1-1/2", 2", 3", 4"  
**Type:** Rotating Rod      **Spring Compressed:** 7 lbs. **Spring At Rest:** 2 lbs.  
**Options:** MB, B, H, V, S, N      For magnetic bumpers add .312

For S option add .250

