



1 1/4" BORE STAINLESS STEEL CYLINDER


Note: The 1 1/4" bore is also available with a 7/16-20 threaded rod. Order -LR option.

SDR-20-□-□

Double Acting



Mount: Stud **Standard Stroke Lengths:** 1/2", 1", 1-1/2", 2", 3", 4", 5", 6"
Type: Rotating Rod
Options: C, F, R, MB, B, W, V, P6, P7, P8, S, N For magnetic bumpers add .312
For C, F, R and S option add .312




Nut included, but not shown on drawing
For C, F, & R options use side ported rear head

UDR-20-□-□

Double Acting



Mount: Universal **Standard Stroke Lengths:** 1/2", 1", 1-1/2", 2", 3", 4", 6, 8", 10", 12"
Type: Rotating Rod
Options: C, F, R, MB, B, W, V, P2, P3, P4, P5, P6, P7, P8, N For magnetic bumpers add .312




Furnished without nut(s). See Chart on Page 38.

SDD-20-□-□

Double Acting



Mount: Stud **Standard Stroke Lengths:** 1", 2", 3", 4", 5", 6"
Type: Double Rod
Options: C, F, MB, B, W, V, P6, P7, P8, N For magnetic bumpers add .312




Nuts included, but not shown on drawing

SRR-20-□-□

Reverse Acting



Mount: Stud **Standard Stroke Lengths:** 1/2", 1", 1-1/2", 2", 3", 4"
Type: Rotating Rod **Spring Compressed:** 10 lbs. **Spring At Rest:** 4.5 lbs.
Options: MB, B, H, W, V, N For magnetic bumpers add .312



Nuts included, but not shown on drawing