

Minimatic[®] Actuators

Easily actuated, clearly identifiable panel controls are the hallmark of a professional control system.

Whether the system is a single valve machine control . . . or an operating console for controlling complex pneumatic systems . . . you will find the actuator you require.

The line includes round push buttons, in flush, extended, and mushroom styles. Also included are key locking controls, and twist actuators. An electric switch is also available where a combination of electric and pneumatic switching is desired in a single panel.

As shown in the drawing, a PB-85 is required to connect a push button and a Clippard valve.


Dimensions

Size 22			Size 30		
Model	"A"	"B″	Model	"A″	"B″
PS-P2F	1.156″	0.492″	PL-P2F	1.440″	0.550″
PS-P2E	1.156″	0.736″	PL-P2E	1.440″	0.960″
PS-P2M	1.575″	0.965″	PL-P2M	1.575″	1.043″
PS-L3M	1.575″	0.965″	PL-L3M	1.575″	1.043″
PS-P4K	1.156″	2.320″	PL-P4K	1.440″	2.280″
PS-L4M	1.575″	2.320″	PL-L4M	1.575″	2.280″
PS-T2T	1.156″	1.043″	PL-T2T	1.440″	1.403″
PS-T3T	1.156″	1.043″	PL-T3T	1.440″	1.043″
PS-T3K	1.156″	2.320″	PL-T3K	1.440″	2.280″

Actuator Mounting Chart

The following chart gives the necessary spacing required between the shoulder of the valve and the base of the adapter.

Valves	PB-85	
MAV-2, -2P, -2R, -3R, -3, -3P MAVO-2, -3	None	
MJV-2, -3 MJVO-2, -3	1/8″	
MAV-4, -4D MJV-4, -4D	None	
ES-1	None	
FV-3, -3P, -3D, -3DP FV-4, -4P, -4D, -4DP FV-5, -5P, -5D, -5DP	1/8″	



Manual Actuator Features

- Attractive and rugged: precision molded ABS plastic
- Two sizes: 30 mm (1 13/64" dia.) in 20 models 22 mm (7/8" dia.) in 20 models
- 4 bright colors for visibility and operator recognition
- Flush, extended, and mushroom styles
- Custom adapter mates manual actuator with 26 different Clippard 2-, 3-, and 4-way valves. Valve and adapter slide on and lock onto actuator in seconds. Easily removed.
- Special wrench fits both sizes, speeds assembly
- Actuators may be mounted or dismounted in panel independent of valve and adapter
- 19 legend plates available plus blank plates in each size
- Valve and adapter may be locked onto actuator in any of four positions to ease installation inside panel
- Anti-rotation rings available for secure mounting
- · Key lockable push buttons for security and/or safety