


Minimatic[®] Cams



Minimatic Sequence Programmer Cams. Use with Clippard MSP or DSP sequence programmers.

Available in 8 models pre-cut with lobes from 15° to 340°, also blank 360° cam for custom machining.



 Order No.
 Lobe
 Order No.
 Lobe


 C-33-15
 ...15'
 C-33-180
 ...180°

 C-33-30
 ...30'
 C-33-270
 ...270°

 C-33-60
 ...60'
 C-33-340
 ...340°

 C-33-90
 ...90'
 C-33-360
 ..uncut*

Vacuum Gauge



Gauge measures pneumatic vacuum pressure. Mounting bracket included.

Range: Scale reading from 0 to 30 in.Hg. and 0 to -1 bar

Construction: Nickel-plated steel case. Plastic face. Dial shows two ranges; Hg in black. bars in red. Built-in pressure snubber.

Ports: Connection located at rear is double threaded O.D. - male thread 1/8" NPT I.D. - tapped for #10-32 fitting

Mounting: Stud mount using 1/8" NPT center stud or panel mount using the zinc plated steel bracket supplied.


Part No.DescriptionVG-30.......Vacuum Gauge

Adjustable Cams



Use with Clippard MSP or DSP sequence programmers. Available in five models with adjustable lobes covering from 30° to 360°,

also as a blank for custom machining.



Lobe Adjustm	nent
From	То
.30°	50°
.45°	80°
.70°	.130°
.120	.230°
.210°	.360°
uncut	
	.30° .45° .70° .120 210°



Gauge measures pneumatic system pressure. Stud mounted.

- Range: Scale reading from 0 to 100 psig and 0 to 6.9 bar
- **Construction:** Steel case. Plastic face. Dial shows two ranges; psig in black. Bars in red. Built-in pressure snubber.

Ports: Connection located at rear is double threaded O.D. - male thread 1/8" NPT I.D. - tapped for #10-32 fitting

Mounting: Direct with 1/8" NPT

 Part No.
 Description

 PG-101-BK
 . Pressure Gauge, Black Case


 PG-101-NP
 . Pressure Gauge, Nickel-Plated

Detent Cams




One standard phenolic detent cam with 4, 6, 8, 10 or 12 evenly spaced cuts is required with each DSP. Special cut detent cams are

available at nominal cost.



Order No.	Number of Positions
DC-4	
DC-6	6
DC-8	8
DC-10	10
DC-12	12

Pressure Gauge



Gauge measures pneumatic system pressure. Mounting bracket included.

- Input Pressure: Scale reading from 0 to 100 psig and 0 to 6.9 bar
- **Construction:** Nickel-plated steel case. Plastic face. Dial shows two ranges; psig in black. Bars in red. Built-in pressure snubber.
- Ports: Connection located at rear is double threaded O.D. - male thread 1/8" NPT I.D. - tapped for #10-32 fitting
- Mounting: With zinc plated steel bracket supplied

Part No. Description PG-100 Pressure Gauge