



NEW! MAXIMATIC® SOLENOID VALVES

Valve Series Enter

Electronic E

Air Pilot A

Valve Type Enter

2-Way (Direct-Acting only) 2

3-Way 3

4-Way 4

Body/Port Size Enter

Direct-Acting

1/8" NPT P

1/8" NPT Stacking S

1/4" NPT Q

Spool Type

#10-32 1N

1/8" NPT 1P

1/4" NPT (0.89 Cv) 2Q

1/4" NPT (1.68 Cv) 3Q

3/8" NPT 3W

1/2" NPT 4Z

Primary/Secondary Actuator Enter

Air/Air AA

Air/Spring AS

Electronic Pilot/Elec. Pilot EE

Electronic Pilot/Spring ES

Direct Acting/Spring DS (2- or 3-Way, #10-32, 1/8", 1/4" only)

Mounting Enter

Standard Manifold (blank)

Actuator/NAMUR* B

* Only available on 3- or 4-Way Electronic Valves. 1/4" NPT Actuator or 3/8" NPT NAMUR Mount.

Spool Type Enter

2-Position, Spool (blank)

3-Position, Closed Center C

3-Position, Exhaust Center E

3-Position, Pressure Center P

Only available on 4-Way Valves with "AA" or "EE" Actuator. Standard Manifold Mount only.

Electrical Connector Enter

DIN Connector D

Wire Leads (18") W

Only required on Electronic Valves.

Voltage Enter

12-Volt DC 012

24-Volt DC 024

24-Volt AC 24A

110-Volt AC 110

220-Volt AC 220


Only required on Electronic Valves.



Single Solenoid Electronic Valves Mounted on 8-Station Manifold

This numbering schematic is shown for illustration purposes only. All possible configurations are not available. For standard models, see the products illustrated in this catalog.

MM



Example: MM - -