

































MINIMATIC® SLIP-ON FITTINGS

SWIVEL FITTINGS

| | | | | | |
|--------------|--|--------------|---|-----------------|---|
| S42-2 |   <p>0.531 1.062 2 (2) 1/16" I.D. hose barb 5/16" hex. 1/8" I.D. hose barb</p> | S44-4 |   <p>0.656 1.187 2 (3) 1/8" I.D. hose barb 5/16" hex.</p> | S40-4004 |   <p>0.937 0.875 5/16" hex. (3) 1/8" I.D. hose barb</p> |
|--------------|--|--------------|---|-----------------|---|

#10-32 to Hose Swivel "T" Fittings

| | | | | | |
|-----------------|--|-----------------|--|-----------------|---|
| ST0-2002 |   <p>0.718 0.718 2 (2) 1/16" I.D. hose barb 5/16" hex. #10-32 thd.</p> | ST0-3003 |   <p>0.801 0.718 2 (2) 3/32" ID hose barb 5/16" hex. #10-32 thd.</p> | ST0-4004 |   <p>0.937 0.718 2 (2) 1/8" I.D. hose barb 5/16" hex. #10-32 thd.</p> |
| ST2-2 |   <p>0.531 0.937 2 (2) 1/16" I.D. hose barb 5/16" hex. #10-32 thd.</p> | ST3-3 |   <p>0.580 0.961 2 (2) 3/32" I.D. hose barb 5/16" hex. #10-32 thd.</p> | ST4-4 |   <p>0.656 1.187 2 (2) 1/8" I.D. hose barb 5/16" hex. #10-32 thd.</p> |
| SP0-2002 |   <p>0.718 0.843 2 (2) 1/16" I.D. hose barb 7/16" hex. 1/8-27 NPT</p> | SP0-3003 |   <p>0.812 0.843 2 (2) 3/32" I.D. hose barb 7/16" hex. 1/8-27 NPT</p> | SP0-4004 |   <p>0.656 0.843 2 (2) 1/8" I.D. hose barb 7/16" hex. 1/8-27 NPT</p> |
| SP2-2 |   <p>0.625 1.031 2 (2) 1/16" I.D. hose barb 7/16" hex. 1/8-27 NPT</p> | SP3-3 |   <p>0.656 1.062 2 (2) 3/32" I.D. hose barb 7/16" hex. 1/8-27 NPT</p> | SP4-4 |   <p>0.718 1.156 2 (2) 1/8" I.D. hose barb 7/16" hex. 1/8-27 NPT</p> |

Tip Most Clippard #10-32 threaded fittings require no more than 9 inch pounds of torque to seal. We recommend that this force not be exceeded.