



3/4" BORE CORROSION RESISTANT CYLINDER


CR-SDD-12-□-□

Mount: Stud
Type: Double Rod

Standard Stroke Lengths: 1", 2", 3", 4", 5", 6"

Options: M, V, N, P2, P3, P4, P5, P6, P7, P8

Double Acting



Furnished without nut(s). Order Part No. [N10-18-SS](#).


CR-SDR-12-□-□

Mount: Stud
Type: Rotating Rod

Standard Stroke Lengths: 1/2", 1", 1-1/2", 2", 3", 4", 5", 6"

Options: M, V, N, P6, P7, P8

Double Acting



Furnished without nut(s). Order Part No. [N10-18-SS](#).


CR-UDR-12-□-□

Mount: Stud
Type: Rotating Rod

Standard Stroke Lengths: 1/2", 1", 1-1/2", 2", 3", 4", 5", 6", 8", 10", 12"

Options: M, V, N, P2, P3, P4, P5, P6, P7, P8

Double Acting



Furnished without nut(s). Order Part No. [N10-18-SS](#).

Stainless Steel Mounting

Foot Bracket

Model Number: [FB-1791-SS](#)

Nut

Model Number: [N10-18-SS](#)

Max. Torque in lbs.: 12

