



**NEW! MAXIMATIC® AIR VALVES**

# Maximatic®



## Maximatic Air Valves

Clippard's Maximatic Air Pilot Valves are available in 3- and 4-way configurations in port sizes from #10-32 thread to 1/2" NPT. They are spool type valves with single or double air pilots with pressure ranges from 0 to 125 psig. Some of the many features of the valve include small size, high flow and competitive pricing.

These valves offer maximum flow in a small package, and are constructed of aluminum, stainless steel and thermoplastic materials. They have a 1/8" NPT external pilot port.

This new line of valves is especially well-suited for packaging, factory automation and OEM fluid power applications.

**Type:** Spool

**Medium:** Air (40 micron filtration) or Inert Gas

**Operating Range:** Single Air Pilot: 20 to 125 psig; all others: see chart below

**Materials:** Aluminum, Stainless Steel, Thermoplastic

**Mounting:** Body Ported, Manifold Mount

**Maximum Pressure:** 125 psig

**Temperature Range:** 32 to 150°F (0 to 65°C)

**Seals:** Buna-N

Conforms to ISO 19973-2 test standards.

### Minimum Pilot Pressure

	Single Pilot		Double Pilot		Three Position	
Operating Pressure (psig)	20	80	20	80	20	80
Pilot Pressure (psig)	20	35	5	8	20*	20*

\* 30 on MMA-41 Series

### 3- & 4-Way Valves

Port	Cv	Flow Rate	
		@ 50 psig	@ 100 psig
#10-32	0.58	16 scfm	27 scfm
1/8" NPT	0.67	18 scfm	31 scfm
1/4" NPT	0.89	26 scfm	49 scfm
3/8" NPT	1.68	51 scfm	93 scfm
1/2" NPT	2.79	91 scfm	171 scfm