

MAXIMATIC® SOLENOID VALVES



Valve Series	Enter	<input type="text"/>
Electronic	E	<input type="text"/>
Air Pilot	A	
Valve Type	Enter	<input type="text"/>
2-Way (Direct-Acting only)	2	<input type="text"/>
3-Way	3	
4-Way	4	
Body/Port Size	Enter	<input type="text"/>
Direct-Acting		<input type="text"/>
1/8" NPT	P	
1/8" NPT Stacking	S	
1/4" NPT	Q	
Spool Type		<input type="text"/>
#10-32	1N	<input type="text"/>
1/8" NPT	1P	
1/4" NPT (0.89 Cv)	2Q	
1/4" NPT (1.68 Cv)	3Q	
3/8" NPT	3W	
1/2" NPT	4Z	
Primary/Secondary Actuator	Enter	<input type="text"/>
Air/Air	AA	<input type="text"/>
Air/Spring	AS	
Electronic Pilot/Elec. Pilot	EE	
Electronic Pilot/Spring	ES	
Direct Acting/Spring	DS (2- or 3-Way, #10-32, 1/8", 1/4" only)	
Mounting	Enter	<input type="text"/>
Standard Manifold	(blank)	<input type="text"/>
Actuator/NAMUR*	B	
		* Only available on 3- or 4-Way Electronic Valves. 1/4" NPT Actuator or 3/8" NPT NAMUR Mount.
Spool Type	Enter	<input type="text"/>
2-Position, Spool	(blank)	<input type="text"/>
3-Position, Closed Center	C	
3-Position, Exhaust Center	E	
3-Position, Pressure Center	P	
		Only available on 4-Way Valves with "AA" or "EE" Actuator. Standard Manifold Mount only.
Electrical Connector	Enter	<input type="text"/>
DIN Connector	D	<input type="text"/>
Wire Leads (18")	W	
		Only required on Electronic Valves.
Voltage	Enter	<input type="text"/>
12-Volt DC	012	<input type="text"/>
24-Volt DC	024	
24-Volt AC	24A	
110-Volt AC	110	
220-Volt AC	220	
		Only required on Electronic Valves.



Single Solenoid Electronic Valves Mounted on 8-Station Manifold

Note: This numbering schematic is shown for illustration purposes only. All possible configurations are not available. For standard models, see the products illustrated in this catalog.

MM



Example: **MM****E**-**4****2Q****ES**-**D****110**