

## R-323



### 3-Way Combination Valve

#### Features:


- Indicator shows valve in shaded position
- Multiple valves save space
- Micro gap construction - snap action and no blow by
- Balanced design allows speed control at exhausts

#### Performance:

**Flow:** 9 scfm @ 100 psig; 255 l/min @ 6.9 bars  
**Pilot Pressure Minimum:** 40 psig; 2.8 bars  
**Temperature:** 32° to 180° F  
**Working Pressure:** 0 to 150 psig; 0 to 10.3 bars

#### Description:

R-323 is a 3-way, spring return, fully ported valve with an independent shuttle valve in the same body. Both valves may be used independently in a circuit. The 3-way can be used normally-OPEN, normally-CLOSED; as a diverter, or as a selector. The R-323 also features an auxiliary pilot on the spring side of the valve.



## R-324



### 3-Way Combination Valve

#### Features:

- Indicator shows valve in shaded position
- Multiple valves save space
- Micro gap construction - snap action and no blow by
- Balanced design allows speed control at exhausts

#### Performance:

**Flow:** 9 scfm @ 100 psig; 255 l/min @ 6.9 bars  
**Pilot Pressure Minimum:** 20 psig; 1.4 bars  
**Temperature:** 32° to 180° F  
**Working Pressure:** 0 to 150 psig; 0 to 10.3 bars

#### Description:

R-324 is a 3-way, two position, fully ported valve with an independent shuttle valve in the same body. Both valves may be used independently in a circuit. The 3-way can be used normally-OPEN, normally-CLOSED; as a diverter, or as a selector.

