

# BRASS BARB TO #10-32 FITTINGS



**Material:** Brass

**Gasket:** Buna-N furnished in package only  
Replacement [11761-2](#)

**Options:** (-ENP), (-M5 on [11752-2](#), [11752-3](#), [11752-4](#) and [11752-5](#))

Hose Barb		
1/16" ID	3/32" ID	1/8" ID
<b>12841*</b>	<b>12843*</b>	<b>12842*</b>
<b>11752-2 &amp; 11752-2-M5 (metric)</b>	<b>11752-8</b>	<b>11752-1</b>
	<p>* Gasket not required; use thread sealant.</p> <p>Tighten by hand for flush mounting in #10-32 threaded holes.</p>	<p><b>#1 Recommended</b></p>
<b>11752-5 &amp; 11752-5-M5 (metric)</b>		<b>11752-4 &amp; 11752-4-M5 (metric)</b>
		<b>11752-3 &amp; 11752-3-M5 (metric)</b>

## BRASS BARB TO #10-32 FITTINGS WITH CAPTIVATED O-RINGS

**Material:** Brass

**Seal:** Buna-N o-ring furnished installed

**Options:** (-ENP)

Hose Barb		
1/16" ID	3/32" ID	1/8" ID
<b>11792-5</b>	<b>11792-8</b>	<b>11792-4</b>