

# 3/4" BORE STAINLESS STEEL CYLINDER




## UDR-12-□-□

Double Acting



**Mount:** Universal      **Standard Stroke Lengths:** 1/2", 1", 1-1/2", 2", 3", 4", 5", 6", 8", 10", 12"  
**Type:** Rotating rod      **Maximum Stroke:** 41"  
**Options:** C, F, R, B, W, V, P2, P3, P4, P5, P6, P7, P8, M, N      For B option add 0.500




Furnished without nut(s). See Chart on Page 24.

## SDR-12-□-□

Double Acting



**Mount:** Stud      **Standard Stroke Lengths:** 1/2", 1", 1-1/2", 2", 3", 4", 5", 6"  
**Type:** Rotating Rod      **Maximum Stroke:** 42"  
**Options:** C, F, R, B, W, V, P6, P7, P8, S, M, N      For B option add 0.500  
 For C, F, R & S options add 0.437




Nuts included, but not shown on drawing  
 C, F, & R options use side ported rear head

## SDD-12-□-□

Double Acting



**Mount:** Stud      **Standard Stroke Lengths:** 1", 2", 3", 4", 5", 6"  
**Type:** Double Rod      **Maximum Stroke:** 20"  
**Options:** C, F, B, W, V, P6, P7, P8, M, N      For B option add 0.500




Nuts included, but not shown on drawing

## SDH-12-□-□

Double Acting



**Mount:** Stud      **Standard Stroke Lengths:** 1", 2", 3", 4", 5", 6"  
**Type:** Hollow Rod      **Maximum Stroke:** 20"  
**Options:** B, W, V, P6, P7, P8, M, N      For B option add 0.500



Nuts included, but not shown on drawing