

Maximatic® Valves Ordering Guide

Valve Series	Enter	<input type="text"/>
Electronic	E	<input type="text"/>
Air Pilot	A	

Valve Type	Enter	<input type="text"/>
2-Way (Direct-Acting only)	2	<input type="text"/>
3-Way	3	
4-Way	4	

Body/Port Size	Enter	<input type="text"/>
Direct-Acting		<input type="text"/>
1/8" NPT	P	
1/8" NPT Stacking	S	
Spool Type		<input type="text"/>
#10-32	1N	
1/8" NPT	1P	
1/4" NPT (0.89 Cv)	2Q	
1/4" NPT (1.68 Cv)	3Q	
3/8" NPT	3W	
1/2" NPT	4Z	

Primary/Secondary Actuator	Enter	<input type="text"/>
Air/Air	AA	<input type="text"/>
Air/Spring	AS	
Electronic Pilot/Electric Pilot	EE	
Electronic Pilot/Spring	ES	
Direct Acting/Spring	DS (2- or 3-Way, #10-32, 1/8", 1/4" only)	

Mounting	Enter	<input type="text"/>
Standard Manifold	(blank)	* Only available on 3- or 4-Way Electronic Valves. 1/4" NPT Actuator or 3/8" NPT NAMUR Mount.
Actuator/NAMUR*	B	

Spool Type	Enter	<input type="text"/>
2-Position, Spool	(blank)	Only available on 4-Way Valves with "AA" or "EE" Actuator. Standard Manifold Mount only.
3-Position, Closed Center	C	
3-Position, Exhaust Center	E	
3-Position, Pressure Center	P	

Electrical Connector	Enter	<input type="text"/>
DIN Connector	D	Only required on Electronic Valves.
Wire Leads (18")	W	

Voltage	Enter	<input type="text"/>
12-Volt DC	012	Only required on Electronic Valves.
24-Volt DC	024	
24-Volt AC	24A	
110-Volt AC	110	
220-Volt AC	220	



Example: MM - -



MME-4ZEE-D



MMA-33WAS

This numbering schematic is shown for illustration purposes only. All possible configurations are not available. For standard models, see the products illustrated in this catalog.



Maximatic® FRL Ordering Guide

Type	Enter	Enter					
FRL	FRL	Filter	F	<input type="text"/>			
Stacking FRL	FRLS	Regulator	R		<input type="text"/>		
Stacking Filter-Regulator	FRS	Lubricator	L			<input type="text"/>	
Body/Port Size	Enter	Enter					
#10-32	.1N	3/8" NPT (High Flow)	.4W				
1/8" NPT	.2P	1/2" NPT	.4Z				
1/4" NPT (Standard Flow)	.2Q	3/4" NPT	.4A				
1/4" NPT (High Flow)	.3Q	1" NPT	.5B				
3/8" NPT (Standard Flow)	.3W						
Options							
		Automatic Drain (D)			Metal Bowl (M)	30 psig (P30) 60 psig (P60)	5 Micron Filter (F5)
		<input type="text"/>			<input type="text"/>	<input type="text"/>	<input type="text"/>

MM - -

Example: MM - -



This numbering schematic is shown for illustration purposes only. All possible configurations are not available. For standard models, see the Maximatic Product Catalog or Price List.

