



Corrosion-Resistant Electronic Valves

CR-EC-2-24-H



2-Way Elec. Valve, N-C, In-Line Mount, Pin Connector, 24 VDC

2D Drawings	2D Files
Accessories	Installation Socket Torque Tool 30215
Coil Resistance	486
Connection	Terminal Pin, 0.025"
Connector	C2-RB18
Current	0.028A
Cycle Life	>1,000,000,000 (ideal applications)
Data Sheet	Data Sheet
Filtration	40 micron (recommended)
Function	2-Way Normally-Closed
Leak Rate	0.1 sccm
Length	1.56
Material, Seals	Nitrile
Material, Spring	ENP Nickel Alloy
Material, Wetted	ENP Brass, ENP Nickel Alloy, 430 Stainless Steel
Max PSI	25 psig
Max. Flow	12.5 l/min @ 25 psig
Medium	Clean, Dry Air & Compatible Gases
Mount	In-Line
Mounting	#6-32 Thread
Operating Pressure	25 psig (12.5 l/min @ 25 psig)
Operating Temperature Range	32 to 150°F (0 to 65°C)
Operating Voltage Range	90 to 110%
Poppet Travel	0.007"
Port Size	#10-32 Female In-Line
Product Line Brochure	Spider Valves
Response Time	5 to 10 milliseconds (nominal)
Unit	Imperial
Voltage	24 VDC
Wattage	1.2 Watts (nominal)
Weight (lbs.)	0.1700
Wire Connector	AMP #103959-1

