



## Proportional Electronic Valves

### ET-PM-10-2530



The EVP 2-Way proportional control valves combine the features of the existing EV series valve—long life, low power, and Clippard's reputation for high quality components—with the additional capability for proportional control. The EVP series valve provides air or gas flow control, and varies the output flow based on the current input to the solenoid.

Controllability and overall value are the main features of the EVP series. The consistent gain of this valve provides a high degree of control for many applications. The valve may be controlled using DC current, open- or closed-loop control, and even PWM to cover a broad range of applications.

2D File	<a href="#">2D File</a>
Accessories	Valve Driver in Enclosure <a href="#">EVPD-2</a> , Valve Driver Board <a href="#">EVPD-1</a> , DIN Rail Mounting Clip <a href="#">EVPD-2DIN</a> , Installation Socket Torque Tool <a href="#">30215</a>
Coil Resistance	54 $\Omega$ @ 73°F (23°C)
Connection	0.110" Terminal Spades
Connector P/N	<a href="#">ET-C48</a> or <a href="#">ET-C120</a> or <a href="#">3831-1-PKG</a>
Data Sheet	<a href="#">Valve Data Sheet</a> , <a href="#">Driver Data Sheet</a>
Flow Rate	23.5 l/min +/- 10% @ 100 psig
Function	2-Way Normally-Closed Proportional
Input Current Range	0 to 0.185 A
Manifolds	<a href="#">Manifolds</a>
Material, Body	Nickel Plated Brass
Material, Seals	Nitrile
Material, Seat	Stainless Steel
Material, Wetted	ENP Brass, ENP Steel, Stainless Steel
Max Voltage Required	12.4 VDC
Max. Flow	±10% of Target Flow
Max. psig	100 psig (7 bar)
Maximum Hysteresis	10% of Full Current
Medium	Clean, Dry Air or Inert Gases
Mounting Holes	Manifold
Number of Ports	2
Operating Instructions	<a href="#">Operating Instructions</a>
Operating Pressure	30 psig (2,1 bar)
Operating Temperature Range	32 to 120°F (0 to 48°C)
Orifice	0.025" Orifice
Poppet Travel	0.007" (0.2 mm)
Porting	#10-32
Ports	ENG Male Stud (Manifold)
Price	79.15
Product Line Brochure	<a href="#">Proportional Valves</a>
Unit	Imperial
Voltage	10 VDC
Wattage	1.9 Watts at 73°F (23°C), 2.4 Watts Max
Weight (lbs.)	0.1700

