



## Fill & Bleed Valves

### FBV-3DPFH



Fill and Bleed Valves may be used to pressurize or "fill" a chamber or bladder by depressing the toggle in one direction and then de-pressurize or "bleed" that same chamber or bladder by depressing the toggle in the other direction. Toggling back and forth between the inlet and exhaust provides a fine adjustment of the required pressure in the chamber or bladder.

|                                   |                                                   |
|-----------------------------------|---------------------------------------------------|
| <b>Actuation</b>                  | Detented/Detented                                 |
| <b>Air Flow</b>                   | 125 l/min @ 50 psig; 210 l/min @ 100 psig         |
| <b>Data Sheet</b>                 | <a href="#">Data Sheet</a>                        |
| <b>Force for Full Stem Travel</b> | 8 oz. Nominal                                     |
| <b>Included Item(s)</b>           | Nut & Lockwashers                                 |
| <b>Input PSI</b>                  | 120 max                                           |
| <b>Material, Body</b>             | Brass Body, Stainless Steel Stem & Spring         |
| <b>Material, Seals</b>            | Nitrile                                           |
| <b>Material, Toggle</b>           | Nickel Plated Brass                               |
| <b>Medium</b>                     | Air                                               |
| <b>Mount</b>                      | #5/8-32 Thread. Two 0.171" mounting holes in body |
| <b>Operating Pressure</b>         | 120 psig max. (8.3 bar)                           |
| <b>Ports</b>                      | 1/8" NPT                                          |
| <b>Product Line Brochure</b>      | <a href="#">Mechanical Valves</a>                 |
| <b>Weight (lbs.)</b>              | 0.2100                                            |

