

# Clippard

## #10-32 & 1/8" NPT Valves

### MJTV-3



These #10-32 ported 2-Way, 3-Way and 4-Way valves are manually-actuated with a toggle. The toggles are NP steel and have a detent action. The MTV-5 has threaded exhaust and can be connected in a dual inlet pressure configuration.

<b>Flow</b>	400 l/min @ 50 psig; 710 l/min @ 100 psig
<b>Force to Rotate Toggle</b>	16 oz. Nominal
<b>Function</b>	3-Way Normally-Closed
<b>Included Item(s)</b>	Nut & Lockwashers
<b>Input PSI</b>	300 psig max.
<b>Material, Body</b>	Brass
<b>Material, Seals</b>	Nitrile Std. FKM or Krytox optional
<b>Material, Spring</b>	Stainless Steel Stem & Spring
<b>Material, Toggle</b>	Nickel-Plated Steel
<b>Max PSI</b>	300 psig
<b>Medium</b>	Air, Water or Oil
<b>Mount</b>	#15/32-32 Thread
<b>Operating Temperature Range</b>	32 to 230 F
<b>Port, Inlet / Port, Outlet</b>	1/8" NPT / 1/8" NPT
<b>Product Line Brochure</b>	<a href="#">Mechanical Valves</a>
<b>Style</b>	Toggle
<b>Unit</b>	Imperial
<b>Weight (lbs.)</b>	0.3000

