



## MMA-41PAAC



1/8" NPT 5 Port 4-Way Spring Ctr. Dbl. Pilot Actuated Air Valve  
w/Closed Center

|                          |                             |
|--------------------------|-----------------------------|
| <b>Air Flow</b>          | 650 l/min @ 100 psig        |
| <b>Max PSI</b>           | 125 psig                    |
| <b>Medium</b>            | Air                         |
| <b>Mount</b>             | Body Ported, Manifold Mount |
| <b>Seals</b>             | Nitrile                     |
| <b>Temperature Range</b> | 32 to 150°F                 |



| Dim. | MMA-41 | MMA-42 | MMA-43 | MMA-44 |
|------|--------|--------|--------|--------|
| DS   | 0.13   | 0.17   | 0.17   | 0.22   |
| DT   | 0.13   | 0.13   | 0.17   | 0.17   |
| H    | 1.06   | 1.38   | 1.57   | 1.97   |
| HS   | 0.16   | 0.28   | 0.27   | 0.30   |
| L    | 3.78   | 4.37   | 5.12   | 6.26   |
| LE   | 1.08   | 1.42   | 1.77   | 2.48   |
| LO   | 0.61   | 0.83   | 0.94   | 1.42   |
| LS   | 0.55   | 0.79   | 0.94   | 1.10   |
| LT   | 1.18   | 1.50   | 1.97   | 2.83   |
| T    | 0.71   | 0.87   | 1.06   | 1.34   |
| TO   | 0.00   | 0.06   | 0.08   | 0.08   |
| TU   | 0.51   | 0.67   | 0.79   | 1.06   |

