

Clippard

MMA-42QAAE



1/4" NPT 5 Port 4-Way Spring Ctr. Dbl. Pilot Actuated Air Valve
w/Exhaust Center

| | |
|--------------------------|-----------------------------|
| Air Flow | 1400 l/min @ 100 psig |
| Max PSI | 125 psig |
| Medium | Air |
| Mount | Body Ported, Manifold Mount |
| Seals | Nitrile |
| Temperature Range | 32 to 150°F |



| Dim. | MMA-41 | MMA-42 | MMA-43 | MMA-44 |
|------|--------|--------|--------|--------|
| DS | 0.13 | 0.17 | 0.17 | 0.22 |
| DT | 0.13 | 0.13 | 0.17 | 0.17 |
| H | 1.06 | 1.38 | 1.57 | 1.97 |
| HS | 0.16 | 0.28 | 0.27 | 0.30 |
| L | 3.78 | 4.37 | 5.12 | 6.26 |
| LE | 1.08 | 1.42 | 1.77 | 2.48 |
| LO | 0.61 | 0.83 | 0.94 | 1.42 |
| LS | 0.55 | 0.79 | 0.94 | 1.10 |
| LT | 1.18 | 1.50 | 1.97 | 2.83 |
| T | 0.71 | 0.87 | 1.06 | 1.34 |
| TO | 0.00 | 0.06 | 0.08 | 0.08 |
| TU | 0.51 | 0.67 | 0.79 | 1.06 |

