



## NPP Pneumatic Pinch Valves



NPP Series 2-Way pneumatic pinch valves are air-piloted devices designed to open or close tubes for controlling flow of liquids and gases. Other valve types have internal passages that may cause small amounts of fluid to remain in the valve. Pinch valves have no areas or dead volume where fluid can become trapped. Only the inside of the tubing has contact with the fluid.

Common industries that utilize pinch valves for the benefit of isolating fluid from a mechanical valve including drug dispensing, laboratory equipment, wastewater, medical devices, chemical, food and beverage equipment, ceramic/glass/plastic, and solids handling.

<b>Data Sheet</b>	<a href="#">Data Sheet, Panel Mount Info</a>
<b>Documentation</b>	CE, RoHS ( <a href="#">Download</a> )
<b>Material, Body</b>	Aluminum, ENP
<b>Material, Wetted</b>	Polyurethane Tubing (no wetted areas in valve)
<b>Max. Pilot Pressure</b>	250 psig (17 bar)
<b>Medium</b>	Air, Water, Gas & Compatible Fluids
<b>Mounting</b>	#4-40 Threaded Holes
<b>Operating Temperature Range</b>	32 to 230°F (0 to 110°C)
<b>Product Line Brochure</b>	<a href="#">Isolation Valves</a>
<b>Tubing, Length</b>	Comes with 12" (305 mm) of selected tubing. Additional tubing available separately.

