



Straight Union

PQC-SU05-BLK



Push-In Fittings, Stainless Steel - Straight Union

2D Drawings	PDF
Material, Body	316L Stainless Steel
Material, Gripper	303 Stainless Steel
Material, Release Collet	316L Stainless Steel
Material, Seals	FKM
Operating Pressure	Vacuum - 290 psi
Operating Temperature Range	0-375° F
Package	Bulk
Tubing	Nylon, PE, PU, Copper
Tubing OD	5/32" (4 mm)
Unit	Imperial
Weight (lbs.)	0.0033

ORDERING INFORMATION

P	Q	C	-		-	
				Tubing		
				<i>Imperial</i>	<i>Metric</i>	Package
				SU05	5/32" (4 mm)	PKG Pack of 1
				SU08	1/4"	BLK Bulk
				SU10	5/16" (8 mm)	
				SU12	3/8"	
				SU16	1/2"	
				SU05	4 mm (5/32")	
				SU06M	6 mm	
				SU10	8 mm (5/16")	
				SU10M	10 mm	
				SU12M	12 mm	
				SU14M	14 mm	
				RU08M06M	8 mm to 6 mm	
				RU10M08M	10 mm to 8 mm	
				RU12M10M	12 mm to 10 mm	

Example Part Number:

PQC-SU05-PKG