

#10-32 & 1/8" NPT Valves

TVO-2M



The function of a 2-Way valve is to turn an air supply on and off. In the "on" position, medium flows from the inlet to the outlet, and in the "off" position, the flow is blocked. 3-Way styles have an exhaust port which vents the outlet to the atmosphere. Available with #10-32 and 1/8" NPT ports.

| | |
|------------------------------------|------------------------------------------|
| Actuation | Momentary |
| Air Flow | 95 l/min @ 50 psig, 160 l/min @ 100 psig |
| Force to Rotate Toggle | 12 oz. Nominal |
| Function | 2-Way Normally-Open |
| Included Items | Nuts & Lockwashers |
| Input PSI | 150 psig (10 bar) max. |
| Material, Body | Brass |
| Material, Seals | Nitrile Std., FKM & Krytox Optional |
| Material, Spring | Stainless Steel Stem & Spring |
| Material, Toggle | Nickel-Plated Steel |
| Medium | Air, Water or Oil |
| Mount | #15/32-32 Thread |
| Operating Pressure | 150 psig (10 bar) max. |
| Operating Temperature Range | 32 to 230°F (0 to 110°C) |
| Ports | #10-32 |
| Product Line Brochure | Mechanical Valves |
| Style | Toggle |
| Unit | Imperial |
| Weight (lbs.) | 0.1000 |

