



## Tee Barb Connector Fittings

### UT0-3002-BLK



Minimatic barb fittings provide a flexible, easy alternative to ferrule and push-to-connect/push-quick fittings. Designed for use with urethane hose, barb fittings will provide a leak-free connection that will hold well beyond the working pressure of the hose without the need for additional clamps.

|                              |                                    |
|------------------------------|------------------------------------|
| <b>Material, Body</b>        | Electroless Nickel Plated Brass    |
| <b>Material, Seal</b>        | Nitrile O-Ring Std., FKM Available |
| <b>Package</b>               | Bulk (Minimum of 250 pc)           |
| <b>Port, Bottom</b>          | #10-32 Male Thread                 |
| <b>Port, Left</b>            | 1/16" Barb                         |
| <b>Port, Right</b>           | 3/32" Barb                         |
| <b>Product Line Brochure</b> | <a href="#">Mechanical Valves</a>  |
| <b>Style</b>                 | Positionable Tee                   |
| <b>Tubing</b>                | <a href="#">1/16" I.D. Tubing</a>  |
| <b>Tubing</b>                | <a href="#">3/32" I.D. Tubing</a>  |
| <b>Weight (lbs.)</b>         | 0.0050                             |
| <b>Wrench Flat</b>           | 5/16" Hex                          |

